


BUILD BETTER



BORGGA PANEL (BP)



Highlights:

- Exposed fastener panel for various applications
- 36" panel coverage
- Ribs 6" on center, 3/4" high
- Purlin bearing leg to simplify installation
- Applies over open framing or solid substrate
- Available in 29 ga., 28 ga., 26 ga., and 24 ga. thickness
- Available in Premium Colors, Standard Colors, acrylic coated zinc-aluminum alloy and bare galvanized finishes

Allowable Load (lbs / ft ²)						
SPANS	29 GA			26 GA		
	I	II	III	I	II	III
3'-0"	62	62	78	78	78	98
3'-6"	46	46	57	58	58	72
4'-0"	34	35	44	43	44	55
4'-6"	24	28	34	30	35	44
5'-0"	17	22	28	22	28	35
5'-6"	13	18	23	16	23	29
6'-0"	10	16	19	13	20	24
6'-6"	8	13	15	10	17	19
7'-0"	6	11	12	8	14	15

I = Simple span II = Two equal Spans
 III = Three equal spans

Effective Panel Properties			
Gauge	Weight Covered Area Galvanized (lbs / ft ²)	I (In ⁴)	S (In ³)
29	0.78	0.0136	0.0254
26	0.98	0.0171	0.0322

Footnotes:

- Load Values Based on Maximum Stress or 1/100 Span Deflection.
- Steel Values Based on 51,000 PSI Yield or Greater
- Values may be increased 1/3 for Wind Loads

The information given on this data sheet has been carefully checked, however, Borgga Steel Buildings & Components does not assume any responsibility for errors or omissions, or any direct or indirect damage caused by incorrect application of the information shown above. Borgga Steel Buildings & Components reserves the right to make changes in any of their specifications or products without any prior notification.

Office phone (559) 834-5375 • Office fax (559) 834-1406
300 West Peach St. • P.O. Box 35 • Fowler, CA 93625
www.borgga.net